



**TELEDYNE** GAS MEASUREMENT INSTRUMENTS  
Everywhereyoulook™



Highly advanced laser technology designed to detect natural gas with the aim of enhancing safety and improving detection for fire services, first responders and utility markets.

## Features

- Quickly scan common venting points from a **Safe Distance**
- Highly visible, sunshine resistant **Guide Laser** equipped for location accuracy
- **Graphical Interface** for easy user interpretation
- **Color Camera** with Bluetooth, WiFi, and datalogging onboard
- **Trusted Technology** used in gas utility since 2005
- Built to **Intrinsic Safety** specifications – submitted certification pending



# Gas Laser

## Specifications

### General

Weight	3 lbs (approx.)
Carry case dimensions	21" x 17.5" x 9.5"
Display	3.5" color LCD
Storage	Internal SD card (not removable)


### Power

Battery	Removable Rechargeable Lithium-ion pack, 10.8 VDC 2.6Ah
Battery Run Time	8 hours at 32°F (approx.)
Battery Charger	External 110-240 VAC, 50/60 Hz Universal
Charge Time	2-3 hours full charge (approx.)
Charging Indicator	Integrated into Dual Battery Charger

### Detection/Measurement System

Detection Method	Tunable Diode Laser Absorption Spectroscopy (TDLAS)
Detection Distance	100 ft (30m) nominal - may vary due to background type and conditions
Measurement Range	0 to 50K PPM-M
Sensitivity	5 PPM-M at distances from 0 to 100 ft (30m)
Beam Size	Conical in shape with a 22" diameter at 100 ft (55cm at 30m)

### Lasers

IR Laser	Class I
Spotter Laser	On time duration is 2 minutes Class 2(II)<2mW @532nm Spot Size is 7mm at 15M
Eye Safety Warning	Do not stare into beam or view directly with optical instrument 

### Display

Resolution	320x240
------------	---------

### Camera

Color	
Aperture	f/2.6
FOV	94DEG (at 6.0mm image circle)

### GPS

Compatible with	GPS / GLONASS / Beidou / Galileo
-----------------	----------------------------------

### Communication

Bluetooth 4.2 BLE (to support future features and mobile applications)	
Wi-Fi	
USB Dual Mode	

### Alarms

Digital Methane Detection (DMD)	Audible tone and visible color border when detection threshold exceeded
Adjustable Detection Alarm Level	
50'	1 to 200 PPM-M
100'	1 to 400 PPM-M
System Fault & Warnings	Audible alarm and visual indication on the display

### Testing

Built-In Self-Test	Verifies operation and adjusts laser wavelength for maximum sensitivity
Test Gas Cell	Integrated within carrying case

### Datalogging

Saves to Internal Memory	FAULT logs Self-Test logs Captures
Data Collected	Includes but not limited to: CH <sub>4</sub> PPM-M measurement GPS location Timestamp Battery level Battery voltage Serial number of the instrument

### Operating Conditions

Operating Temperature	0° to +122°F (-17° to 50°C)
Humidity	5 to 95% RH, non-condensing

### Regulatory

Instrument Protection	IP54 (water splash and dust resistant)
Compliance	EMC (EN61000-6-2, EN6100-6-4)
Radio Equipment Directive	(2014/53/EU) ETSI EN 301 489-1 v2.2.0
EN 61326-1:2013	
47 CFR Part 15 & ICES-003	



We are committed to ensuring the quality and continuous improvement of our products. The information contained in this brochure is therefore subject to change without notice, only the technical data contained in the manual is binding. For more information, please contact us or our distributor.



**AMERICAS**  
14880 Skinner Rd  
Cypress, TX 77429  
USA  
Tel.: +1 713-559-9200

**EMEA**  
Inchinnan Business Park  
Renfrew, PA4 9RG  
Scotland, UK  
Tel : +44 (0)141 812 3211

**ASIA PACIFIC**  
Room 04, 9th Floor  
275 Ruiping Road  
Xuhui District, Shanghai, China  
Tel.: +86-134 8229 5057